

PETROLATUM TAPE

Description Petrolatum Tape is composed of a non-woven synthetic fabric carrier, fully impregnated with a neutral compound based on saturated petrolatum and inert siliceous fillers. The tapes are designed to provide long term corrosion protection to pipes, flanges, valves, and related surfaces.

Typical Applications • Corrosion prevention

- Benefits**
- Applied to marginally prepared surfaces (SSPC SP 2-3)
 - Conforms to irregular shapes and profiles
 - Contains corrosion inhibiting, moisture displacing and flow control additives
 - UV resistant
 - Can be applied to cold, wet surfaces
 - Not effected by water, acid, salts or soil organics
 - Encapsulation of lead paint
 - Contains no solvents or volatile or organic compounds
 - Easy application from arctic to tropical temperatures
 - Ready for immediate service after application
 - Meets AWWA C217 Standard
 - Can be applied above and below ground

Physical Properties Service Temperature: Max: 158°F (70°C)
 Weight: 0.295 lbs/ft² (1.44 kg/m² avg.)
 Roll Widths: 2" to 12" (50 to 300 mm)
 Roll Lengths: 33' (10 m)
 Recommended Primer: Petrolatum Paste Primer

Warranty ©Neptune Research Inc. (NRI) NRI® is a registered trademark. NRI utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact your local NRI distributor or office for the most current product specifications. NRI warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.
 PT DS 0315 English



Innovative Composite Solutions

+1.561.683.6992 • NEPTUNERESARCH.COM